



Recommended P.C.B Layout  
General Tolerances:0.05

- Specifications :
- Voltage rating: 30V AC / DC
  - Current rating: 0.5A AC / DC
  - Withstanding voltage: 200V AC/minute
  - Temperature range: -25°C~+85°C
  - Insulation resistance: ≥100MΩ
  - Contact resistance: ≤20mΩ
  - After environmental testing : ≤30mΩ

Poles	Dimensional(mm)			Poles			Dimensional(mm)		
	A	B	C	A	B	C	A	B	C
02	0.80	1.80	3.78	12	8.80	9.80	11.78		
03	1.80	2.70	4.58	13	9.80	10.70	12.58		
04	2.40	3.50	5.38	14	10.40	11.50	13.38		
05	3.20	4.30	6.18	15	11.20	12.30	14.18		
06	4.00	5.10	6.98	16	12.00	13.10	14.98		
07	4.80	5.90	7.78	17	12.80	13.90	15.78		
08	5.60	6.70	8.58	18	13.60	14.70	16.58		
09	6.40	7.50	9.38	19	14.40	15.50	17.38		
10	7.20	8.30	10.18	20	15.20	16.30	18.18		
11	8.00	9.10	10.98						

J0800WR-XX-4K	PART UL 8V/4 Black (Polypropylene)	Gold-Plated	Gold-Plated	0800H
J0800WR-XX	Phosphor Bronze	Gold-Plated	Gold-Plated	
J0800WR-XX	ULP UL 8V/4 Halogen-free	Th-Plated	Th-Plated	
PART NO	Material	Material(Pin)	Finish(Pin)	Material Finish (Outer Tails)
				Made with HLB Housing

东莞市翰皓精密电子有限公司

PART NO. J0800WR-XX

DONGGUAN HANHAO PRECISION ELECTRONIC CO.,LTD  
0.80mm IDC Style Connectors

2016/11/08	D	E	Modify the appearance	Yuchuan	Jong Lau	GENERAL TOLERANCE	PROJECT	APPROVAL	DATE
2016/07/17	C	D	Add the Part No 6T	Yuh	Jong Lau	±0.30	XX	XX	2016/07/17
2014/05/28	B	C	Change PCB size			±0.20	XXX		2014/05/28
DATE	OLD REV	NEW REV	ECN	CHECK	APPROVAL	±0.10			

DESCRIPTION	CHECK	APPROVAL	DATE
Change PCB size			
W.X.T	CHECK	DATA	2013/08/06
LI Song	DRAWN		
UNIT	SCALE	NUMBER	REV
MM	1:1	A-172	E